




HARDWOOD FLOORING | TECHNICAL INFORMATION



Product # 2-1105-3685



LINE | CHEVRON
COLOR | FLAX

Wood species | Oak
Grade | 1 Natur
Constructions | 2-layer T&G Engineered Flooring
Size | 16,0 x 127 x 548 mm (5/8" x 5" x 21 5/8")
Finish | Resilient Lacquer

CONSTRUCTION : 2-LAYER T&G ENGINEERED FLOORING

DIMENSIONS :			PACKAGING :	
			BOX	PALLET
Thickness	16,0 mm (5/8")		Content: 1,392 m ²	54 (75,168 m ²)
Width	127 mm (5")		Weight: 16 kg	883 kg
Length	548 mm (21 5/8")		H x W x L: 168 x 275 x 681 mm	1144 x 832 x 2050 mm
Average length	-		Content: 15 sq.ft.	809 sq.ft.
Microbevel	0,5 mm		Weight: 35,5lb	1954 lb
Joint type	tongue and groove (T&G)	H x W x L: 7" x 11" x 27"	45" x 33" x 81"	

DEVIATIONS :		
Deviation on Thickness	± 0,2 mm	EN 13489
Deviation on Width	± 0,2 mm	
Height Difference	≤ 0,2 % of width	ГОСТ 862.1
Cup	≤ 0,2 % of plank width	СТБ 1454
Bow	≤ 0,5 % of length	EN 13489
Spring	≤ 0,1 % of length	

CHARACTERISTICS :		
Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,104 m ² ·K/W	
Thermal conductivity	0,154 W/(m·K)	
Structural warranty	Lifetime	

INSTALLATION :	STORAGE AND USAGE :
<p>Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.</p>	<p>— Air humidity 40% – 65% — Temperature +18 °C – +22 °C</p>

FINISH : RESILIENT LACQUER

DESCRIPTION :	
Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores
Sheen	Semigloss 15 - 22 GU/60°
Finish warranty	-

CLASSIFICATION SURFACE CHARACTERISTICS :		
Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438-2
Slip resistance	52 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Resilient Lacquer finish assumes regular (daily if necessary) cleaning from dust and dirt using a vacuum, followed by a thorough cleaning using Coswick hardwood floor cleaner or other similar product.

GRADE : 1 NATUR

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted contrast to 25% of the plank area	Bark pocket	Permitted up to 50 mm in length, up to 5 mm in width, filled
Colour variation	No limit	Pith	Permitted
Knot	Permitted up to 25 mm, filled	Slope of grain	Permitted
Checks	Permitted filled up to 0,5 mm in width	Medullary ray	Permitted